



Solar Powered LED Street Lights

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: JD
- Certification: CE.EMC.LVD
- Model Number: JD-1036A
- Minimum Order Quantity: 1 pcs
- Price: Negotiable
- Packaging Details: 5 layer cartons
- Delivery Time: 15-30days
- Payment Terms: T/T, L/C,
- Supply Ability: 10000pcs/Month



Product Specification

- Material: ADC12 Die Cast Aluminum
- Color: Grey/black/dark Grey
- Ip Rating: IP66
- Working Temperature(): -40 - 49
- Cri (ra>): 75
- Input Voltage(v): 100-240VAC
- Application: Roadway,outdoor,garden
- Warranty(year): 5
- Working Lifetime(hour): 50009
- Rated Power: 30W
- Highlight: commercial solar pole lights

Product Description

IP65 newest type decoration garden solar powered led street light

WIDE APPLICATION - Ideal for outdoor applications such as flood light, security light, post light, street lights, area light, parking lot light.

EASY INSTALLATION: This pole light fits DO 2-3/8 inch pole easy to install the parking lot lighting

5 YEARS WARRANTY: This Post light outdoor fixture is certified by ETL DLC, Design Lights Consortium (DLC) Approved LED Lighting, which ensures better quality, safety and reliability.

IP65 rating for outdoor use.

Outdoor courtyard, garden, road, community wall, roof, villa, gate, balcony, fence, etc.

Features :

- 1. luminaire** placed on the top of the pole, outdoor lighting, suitable for illumination of squares, sidewalks, parks etc.
- 2. Framework and TOP-cover** made of die-casting aluminium.
- 3.** The body has suitable place for its placement on the top of the pole
- 4.** On the upper part there is a special cast-pressed cover for evaporation and also original channels for the moist. Their connection with luminaire is made through copper screw for elegant look.
- 5. DIFFUSER** made of one piece clear **Polycarbonate Cover**, UV stabilized, shock-resistant and resistant to thermal shocks.

Specification :

Model	JD-1036A 30W	JD-1036B 60W	JD-1036C 60W
Wattage	30W	60W	60W
Beam Angle	120 Degree		
Luminous Flux	3000lm	6000lm	6000lm
Color Temperature	2700K~6500K		
Input Voltage	AC100-277V, 50-60Hz		
Life Hours	50,000		
LED Chip	3535/ 3030 smd		
CRI	Ra>80		
PF	>0.92		
Surge Voltage	10V/20KV		
IP Rating	IP66		
Dimension	L554*W377*H305mm		

Product Details :

Product dimension:

BOM pictures :

Product distribution curve :
