



IP66 All In One LED Solar Street Light

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: CLASSIC
- Certification: EMC.LVD TUV ISO9001
- Model Number: JD-S001E
- Minimum Order Quantity: 1 pcs
- Price: Negotiable
- Packaging Details: 6 layer cartons
- Delivery Time: 20days
- Payment Terms: T/T, L/C, D/P, Western Union, D/A
- Supply Ability: 6000pcs/Month



Product Specification

- Material: ADC12 Die Cast Aluminum
- Color: Dark Grey
- Ip Rating: IP66
- Working Temperature(): -55-66
- Lamp Luminous Efficiency(lm/w): 4800
- Working Lifetime(hour): 50016
- Item Type: Solar LED Street Lights
- Light Source: Halogen Bulbs
- Highlight: **solar powered street lights**

Product Description

Hot High Quality Sale All In One Solar Led Street Light Prices IP66

60W Project Microwave sensor integrated LED Solar Street Product features:

- 1, Drawer design ,easy replacement for battery
- 2, Fault detection indicator,user-friendly
- 3, Microwave sensor ,wide induction range 180 degree , with high sensitive .
- 4, LED logo , Pioneer , high end and classy. Working modes:
- 5, Three lighting mode for choice

Certificate :

CE EMC LVD IK08

IEC 60598-2-3: Luminaires – Particular requirements - Luminaires for road and street lighting.

IEC 60529 :Degrees of protection provided by enclosures (IP 66) .

IEC 62262 :Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK08) .

Features :

1. Wall mount & pole mount
2. 1500 cycle Li-ion battery,10 years spen life.
3. Brightness and lighting time adjustable by remote controller
4. ALS2.0 New technology support 6-8 rainy days lighting
5. Professional lighting distribution for wide lighting area
6. Turn on at dusk and tun off at dawn automatically.

Specification :

Model	JD-SL001A 10W	JD-SL001B 15W	JD-SL001C 20W	JD-SL001D 25W	JD-SL001E 30W	JD-SL001F 40W	JD-SL001G 50W	JD-SL001H 60W
Wattage	10W	15W	20W	25W	30W	40W	50W	60W
Beam Angle	150°/50°/120°/120°							
Luminous Flux	3900lm	4800lm	6500lm	7800lm	9100lm	13000	15600lm	19500lm
Color Temperature	2700K~6500K							
Input Voltage	AC100-277V, 50-60Hz							
Life Hours	50,000							
LED Chip	3030							
CRI	Ra>80							
PF	>0.92							
Surge Voltage	10V/20KV							
IP Rating	IP66							
Dimension	573*245*120MM		717*320*130MM		867*392*159MM			

Product Details :



INTEGRATED SOLAR LED STREET LIGHT
一体化太阳能路灯

SOLAR  LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C