



Distance Solar Walkway Lights , 150w Solar Powered Led Garden Lights

Basic Information

Place of Origin: Shenzhen China
Brand Name: Chanpower
Certification: CE FCC ROHS
Model Number: TL-3602
Minimum Order Quantity: 500
Price: negotiable

Packaging Details: Carton

• Delivery Time: 30~35 work days

• Payment Terms: L/C, T/T

• Supply Ability: 2000 sets per month



Product Specification

• Solar Panel: 150w

• LED: CREE 50w

Controller: MPPT Charge Controller

Battery: LiFePO4Application: SquarePole Length: 5-7m

• Highlight: solar powered street lights

Product Description

Distance Solar Walkway Lights, 150w Solar Powered Led Garden Lights

Feature

Average distribution light lens, long pole distance, easy to get the acceptance requirements

Solar Street Light LED Fixture surface with Polyester Substance

Solar Street Light LED Fixture implement of Reflect, Made of High Purity Aluminum

Solar Street Light PV Panel, Glass light distribution, no PC diffuser, once distributing light makes sure only less loss of ray

Solar Street Light PV Panel, Excellent efficiency based on innovative

Solar Street Light battery, Good safety, no risk of explosion

Solar Street Light battery, High temperature performance, electric heating peak is twice that of LiNiCoMnO2 battery

Solar Street Light battery, Real green and environmentally friendly batteries

Solar Street Light battery, Extremely low internal resistance and self-discharge rate

Battery Box Life span: 20years

Solar Street Light Controller, Aluminumhousing

Solar Street Light Controller, Suitable for Lead-acid, LiNiCoMnO2, LiFePO4,LiCoO2 battery, etc.

Solar Street Light Controller, IR and MW sensor optional

Solar Street Light Controller, Charging battery even in 0 Voltage, activate aromatically.

Solar Street Light Pole, New powder paniting methods make sure the surface more smooth, the color can be done as you like.

Solar Street Light Pole, Arm diameter:48&60mm

Parameters

Item		TL-3602	L-3602	TL-3602	TL-3602
Light Style		Split	Split	Split	Split
POWER		40W	45W	50W	55W
	Flux	5400~6600 lm	6075~7425 lm	6750~8250 lm	7425~9075 lm
LED	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	45W	50W	55W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Largest Wattage	120W monocrystalline silicon	135W monocrystalline silicon	150W monocrystalline silicon	165W monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре		Lithium iron phosphate battery 1240WH		Lithium iron phosphate battery 1510WH
	Life	5-8years	5-8years	5-8years	5-8years
Control	Туре	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM
	Charge / time	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time			12hrs every day 3-5 rainning days	12hrs every day 3-5 rainning days
	Normal Setting	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light		Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
	Туре	m]	m]	m]	Cone [Ø60mm/Ø140m m]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating
Pole	Length	5-7M	5-7M	5-7M	5-7M
Pole	Longin	P 7141		O 7141	

Thicknes s	2.5MM	2.5MM	2.5MM	2.5MM
Weight	25-30kg	25-30kg	25-30kg	25-30kg
Flange	250*250mm	250*250mm	250*250mm	250*250mm
Anchor Bolt	2kg	2kg	2kg	2kg



Q: What about the delivery date?

A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.

Q: Do you have any MOQ limit for led light order?

A: for solar street light controller, 1pc for sample checking is available

Q: How do you ship the goods and how long does it take to arrive?

A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

Q: How to proceed an order for solar led street light?

A: Firstly,let us know your requirements or application.

Secondly, Chanpower quote according to your requirements or our suggestions.

Thirdly, customer confirms the details and places deposit for formal order.

Fourthly, Chanpower arrange the production.

Q: Can Chanpower use our my logo on the solar led light products?

A: Yes. Please inform us formally confirm the design before our production.

Q: Do you offer guarantee for the products?

A: Yes, Chanpower offer 3 years warranty to our products.

Q:How to deal with the faulty?

A: Firstly, Please send us some pictures or videos of the faulty item for our analyzation. Our products are produced in strict quality control system and the defective rate will be less than 0.2%.

Secondly, during the guarantee period, Chanpower will send new parts with new order for defective products and Chanpower will assess if it's necessary to return the faulty item, Chanpower can discuss the solution including recall according to real situation.

Q:Can I Get A Lower Price If I Order Large Quantities?

A:Different Order Quantity Different Price, In Addition Any Customized Service Is Available According To Target Price.

Q:Can I Get The Pre-Production solar street controller Sample?

A:Yes, Pre-Production solar street controller Sample Is Available.

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C