



Road / Garden Solar Panel Street Light 50w 6000k Color **Temperature**

Basic Information

. Place of Origin: Shenzhen China . Brand Name: Chanpower CE FCC ROHS · Certification: TL-3702 Model Number: • Minimum Order Quantity: 500 • Price: negotiable · Packaging Details:

• Delivery Time: 30~35 work days

Payment Terms: L/C,T/T

. Supply Ability: 2000 sets per month

Carton



Product Specification

6000k Color Temperature: . LED Flux: 8250lm

PWM / MPPT Charge Controller . Controller:

. LED Fixture: 50w

· Application: Road, Garden, Yard

• MW Sensor: Optional

• Highlight: solar powered street lights

Product Description

Road / Garden Solar Panel Street Light 50w 6000k Color Temperature

Feature

Chanpower Manufactured according to international quality management system(ISO9001)

Solar Street Light LED Fixture is easy to install and handle for various applications

Solar Street Light LED Fixture, High-Pressure Die-casting Aluminum.

Solar Street Light PV Panel, Superior Aluminium alloy material, radiating function is more efficient, make sure long lifespan

Solar Street Light PV Panel, Excellent efficiency based on innovative

Solar Street Light battery, Good safety, no risk of explosion. Use MOSFET as electronic switch, without any mechanical switch

Solar Street Light battery, Long service life, using cells with more than 2000 cycles, life expectancy of more than 5 years

Solar Street Light battery, Environmentally friendly, no heavy metals and rare metals, no poisons and no pollution, in line with RoHS environmental protection regulations

Solar Street Light battery, Working temperature: -0 to +60 centigrade

Battery Box Pressure resistant, Good ventilation, Patented design

12V/24V automatic identify or user-defined working voltage. Solar Street Light Controller, High efficient Series PWM charging, increase the battery lifetime and improve the solar system performance

Solar Street Light Controller,

Solar Street Light Controller, Multiple load control modes, increase the flexibility of the load output

Solar Street Light Pole, Fastener Bolt and Acrews: Stainless Steel

Solar Street Light Pole, Finish Hot-dip Galvanize, powder coating

Parameters

Item		TL-3702	TL-3702	TL-3702	TL-3702
Light Style		Split	Split	Split	Split
POWER		40W	45W	50W	55W
LED	Flux	5400~6600 lm	6075~7425 lm	6750~8250 lm	7425~9075 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	45W	50W	55W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
		120W	135W	150W	165W
Solar Panels	Largest Wattage	monocrystalline silicon	monocrystalline silicon	monocrystalline silicon	monocrystalline silicon
	Life			25years	25years
Battery	Туре	Lithium iron phosphate battery 1100WH	Lithium iron phosphate battery 1240WH	Lithium iron phosphate battery 1380WH	Lithium iron phosphate battery 1510WH
	Life	5-8years	5-8years	5-8years	5-8years
Control		ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM
	Charge / time	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time	Power 24hrs	Power48hrs,Full Power 24hrs	Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time	3-5 rainning days		12hrs every day 3-5 rainning days	
	Normal Setting	Setting, [eg. X% Power Light 1st 4 hours, X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Fixture		Aluminium	Aluminium	Aluminium	Aluminium
	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance	Height 5-7M / Distance10-20M		Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM

		Cone	Cone	Cone	Cone
Pole		[Ø60mm/	[Ø60mm/	[Ø60mm/	[Ø60mm/
		Ø140mm]	Ø140mm]	Ø140mm]	Ø140mm]
	Material	Galvanized	Galvanized	Galvanized	Galvanized Sheet with Coating
		Sheet with	Sheet with	Shoot with	
		Coating	Coating	Coating	
	Length	5-7M	5-7M	5-7M	5-7M
	Thicknes	2.5MM	2.5MM	2.5MM	2.5MM
	s				
	Weight	25-30kg	25-30kg	25-30kg	25-30kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Anchor	2kg	2kg	2kg	2kg
	Bolt				



Q: Do you have any MOQ limit for led light order?

A: for solar street light controller, 1pc for sample checking is available

Q: How do you ship the goods and how long does it take to arrive?

A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

Q: How to proceed an order for solar led street light?

A: Firstly, let us know your requirements or application.

Secondly, Chanpower quote according to your requirements or our suggestions.

Thirdly, customer confirms the details and places deposit for formal order.

Fourthly, Chanpower arrange the production.

Q: Can Chanpower use our my logo on the solar led light products?

A: Yes. Please inform us formally confirm the design before our production.

Q: Do you offer guarantee for the products?

A: Yes, Chanpower offer 3 years warranty to our products.

Q:How to deal with the faulty?

A: Firstly, Please send us some pictures or videos of the faulty item for our analyzation. Our products are produced in strict quality control system and the defective rate will be less than 0.2%.

Secondly, during the guarantee period, Chanpower will send new parts with new order for defective products and Chanpower will assess if it's necessary to return the faulty item, Chanpower can discuss the solution including recall according to real situation.

Q:Can I Get A Lower Price If I Order Large Quantities?

A:Different Order Quantity Different Price, In Addition Any Customized Service Is Available According To Target Price.

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C