



Long Pole Distance Solar Panel Street Light Explosion Proof Lifespan 50000hrs

Basic Information

Place of Origin: Shenzhen China
Brand Name: Chanpower
Certification: CE FCC ROHS
Model Number: TL-3801/02
Minimum Order Quantity: 500

Price: negotiable Packaging Details: Carton

• Delivery Time: 30~35 work days

Payment Terms: L/C, T/T

• Supply Ability: 2000 sets per month



Product Specification

• Solar Panel: 165w

• LED: 55w CREE

• Controller: Charge Controller PWM / MPPT

Battery: LiFePO4Application: Square, Road

• Pole Length: 5-7m

• Highlight: solar walkway lights

Product Description

Long Pole Distance Solar Panel Street Light Explosion Proof Lifespan 50000hrs

Feature

Average distribution light lens, long pole distance, easy to get the acceptance requirements

Solar Street Light LED Fixture is easy to install and handle for various applications

Solar Street Light LED Fixture implement of Reflect, Made of High Purity Aluminum

Solar Street Light PV Panel, Superior Aluminium alloy material, radiating function is more efficient, make sure long lifespan

Solar Street Light PV Panel, with stand heavier snow load and higher wind-pressure.

Solar Street Light battery, Good safety, no risk of explosion

Solar Street Light battery, Long service life, using cells with more than 2000 cycles, life expectancy of more than 5 years

Solar Street Light battery, Real green and environmentally friendly batteries

Solar Street Light battery, Long life design

Battery Box Life span: 20years

Solar Street Light Controller,12V/24V automatic identify or user-defined working voltage

Solar Street Light Controller, High efficient Series PWM charging, increase the battery lifetime and improve the solar system performance

Solar Street Light Controller,LandStar BP has no keys , The control function and the switch condition of the load can be modified by communication connection

Solar Street Light Controller,Use of standard Modbus communication protocol for TTL-232 bus connections, communication protocol compatibility much better

Solar Street Light Pole, Fastener Bolt and Acrews: Stainless Steel

Solar Street Light Pole, Life span: 25years

Parameters

Item		TL-3801/02	L-3801/02	TL-3801/02	TL-3801/02
Light Style		Split	Split	Split	Split
POWER		40W	45W	50W	55W
LED	Flux	5400~6600 lm	6075~7425 lm	6750~8250 lm	7425~9075 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	45W	50W	55W
	Life	50000hrs		50000hrs	50000hrs
Solar Panels	Largest	120W	135W	150W	165W
	Wattage	monocrystalline silicon	monocrystalline silicon	monocrystalline silicon	monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре		Lithium iron phosphate battery 1240WH	Lithium iron phosphate battery 1380WH	Lithium iron phosphate battery 1510WH
	Life	5-8years	5-8years	5-8years	5-8years
Control		ChanPower MPPT / PWM	MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM
		valid for 6 hours of sunshine	of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time	3-5 rainning days	3-5 rainning days		12hrs every day 3-5 rainning days
	Normal Setting	Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light		Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Distance	Distance10-20M	Distance10-20M	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
	Туре	Cone [Ø60mm/Ø140m m]	Cone [Ø60mm/Ø140m m]	Cone [Ø60mm/Ø140m m]	Cone [Ø60mm/Ø140m m]

Pole	1		Galvanized Sheet with Coating	IShoot with	Galvanized Sheet with Coating
			5-7M	5-7M	5-7M
	Thicknes s	2.5MM	2.5MM	2.5MM	2.5MM
	Weight	25-30kg	25-30kg	25-30kg	25-30kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Anchor Bolt	2kg	2kg	2kg	2kg



Q: Can I have a sample order for solar products?

A: Yes, Chanpower welcome sample order to test and check quality. Mixed samples are acceptable, for split style solar street lights is suitable for project according to clients' requirement, normally no sample in stock .

Q: What about the lead time?

A: Accessory sample needs 3-5 days, mass production needs 1-4 weeks for order quantity more than one container.

Q: Are you a factory or a trading company?

A: Chanpower is the factory with high production capacity and product range of solar products in China.

Q: How to choose the system Voltage 12V /24V ?

A: Chanpower could design the system for you. Usually 12V system for 15W-40W LED lamp, 24V system for 50-150W LED lamp.

Q: How do you ship the goods and how long does it take to arrive?

A: Accessory sample shipped by DHL, UPS, FedEx ,TNT etc. It usually takes 3-5 days to arrive. Airline and sea shipping also optional.

Q: What is your Warranty Policy?

A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.

Q: Can I have a sample order for led light?

A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.

Q: What about the delivery date?

A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.

Q: Do you have any MOQ limit for led light order?

A: for solar street light controller, 1pc for sample checking is available

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C