



## Yard 55w Solar Panel Street Light Flux 7425lm Color Temp 4000K IP67 Grade

### Our Product Introduction

#### Basic Information

- Place of Origin: Shenzhen China
- Brand Name: Chanpower
- Certification: CE FCC ROHS
- Model Number: TL-3901/02
- Minimum Order Quantity: 500
- Price: negotiable
- Packaging Details: Carton
- Delivery Time: 30~35 work days
- Payment Terms: L/C, T/T
- Supply Ability: 2000 sets per month



#### Product Specification

- Color Temperature: 4000k
- LED Flux: 7425lm
- Controller: PWM Solar Charge Controller
- LED: CREE 55w
- Application: Parking. Road
- MW Sensor: Optional
- Highlight: solar powered street lights

## Product Description

### Yard 55w Solar Panel Street Light Flux 7425lm Color Temp 4000K IP67 Grade

#### Feature

Chanpower Manufactured according to international quality management system(ISO9001)  
 Solar Street Light LED Fixture is easy to install and handle for various applications  
 Solar Street Light LED Fixture cover, High Stength and High Transparent Toughened Glass  
 Solar Street Light PV Panel,beautifully plate design ,Highly optimized for general use  
 Solar Street Light PV Panel,Glass light distribution,no PC diffuser,once distributing light makes sure only less loss of ray  
 Solar Street Light battery,Good safety, no risk of explosion  
 Solar Street Light battery, Long service life, using cells with more than 2000 cycles, life expectancy of more than 5 years  
 Solar Street Light battery,Extremely low internal resistance and self-discharge rate  
 Solar Street Light battery,Excellent performance in capacity recovery  
 Battery Box Waterproof , IP 67,Antiseptic  
 Solar Street Light Controller,Support firmware upgrade  
 Solar Street Light Controller,Fully encapsulated PCB, IP67 protection  
 Solar Street Light Pole, Arm diameter:48&60mm  
 Solar Street Light Pole,Material Q235, mild steel (Q275 Q345 available)

#### Parameters

Item		TL-3901/02	TL-3901/02	TL-3901/02	TL-3901/02
Light Style		Split	Split	Split	Split
POWER		40W	45W	50W	55W
LED	Flux	5400~6600 lm	6075~7425 lm	6750~8250 lm	7425~9075 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	45W	50W	55W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Largest Wattage	120W monocrystalline silicon	135W monocrystalline silicon	150W monocrystalline silicon	165W monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Type	Lithium iron phosphate battery 1100WH	Lithium iron phosphate battery 1240WH	Lithium iron phosphate battery 1380WH	Lithium iron phosphate battery 1510WH
	Life	5-8years	5-8years	5-8years	5-8years
Control	Type	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM
	Charge / time	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharge / time	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time	12hrs every day 3-5 raining days	12hrs every day 3-5 raining days	12hrs every day 3-5 raining days	12hrs every day 3-5 raining days
	Normal Setting	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light Fixture	Materials	Aluminium	Aluminium	Aluminium	Aluminium
	Style	Selectable	Selectable	Selectable	Selectable
Installation	Height and Distance	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M	Height 5-7M / Distance10-20M
	Installation Hole	Diameter:40-75MM	Diameter:40-75MM	Diameter:40-75MM	Diameter:40-75MM
Pole	Type	Cone [Ø60mm/Ø140mm]	Cone [Ø60mm/Ø140mm]	Cone [Ø60mm/Ø140mm]	Cone [Ø60mm/Ø140mm]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating
	Length	5-7M	5-7M	5-7M	5-7M

Thickness	2.5MM	2.5MM	2.5MM	2.5MM
Weight	25-30kg	25-30kg	25-30kg	25-30kg
Flange	250*250mm	250*250mm	250*250mm	250*250mm
Anchor Bolt	2kg	2kg	2kg	2kg

#### FAQ

Q: What about the lead time?

A: Accessory sample needs 3-5 days, mass production needs 1-4 weeks for order quantity more than one container.

Q: Are you a factory or a trading company?

A: Chanpower is the factory with high production capacity and product range of solar products in China.

Q: How to choose the system Voltage 12V /24V ?

A: Chanpower could design the system for you. Usually 12V system for 15W-40W LED lamp , 24V system for 50-150W LED lamp.

Q: How do you ship the goods and how long does it take to arrive?

A: Accessory sample shipped by DHL, UPS, FedEx ,TNT etc. It usually takes 3-5 days to arrive. Airline and sea shipping also optional .

Q: What is your Warranty Policy?

A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.

Q: Can I have a sample order for led light?

A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.

Q: What about the delivery date?

A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.

Q: Do you have any MOQ limit for led light order?

A: for solar street light controller, 1pc for sample checking is available

Q: How do you ship the goods and how long does it take to arrive?

A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

**SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD**



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C