



Color Temp 6000K Solar Panel Street Light Beautifully Plate Design For Garden

Basic Information

. Place of Origin: Shenzhen China Chanpower . Brand Name: CE FCC ROHS · Certification: TL-5401 Model Number: • Minimum Order Quantity: 500 • Price: negotiable · Packaging Details:

• Delivery Time: 30~35 work days

Payment Terms: L/C, T/T

. Supply Ability: 2000 sets per month

Carton



Product Specification

 Color Temperature: 6000k . LED Flux: 9900lm

MPPT Charge Controller . Controller:

• LED: 60w

· Application: Garden, Outdoor • MW Sensor: Optional IP65 Protection Level:

Material: ABS+Aluminum • Highlight: solar walkway lights

Product Description

Color Temp 6000K Solar Panel Street Light Beautifully Plate Design For Garden

Feature

Average distribution light lens, long pole distance, easy to get the acceptance requirements

Solar Street Light LED Fixture surface with Polyester Substance

Solar Street Light LED Fixture implement of Reflect, Made of High Purity Aluminum

Solar Street Light PV Panel, beautifully plate design, Highly optimized for general use

Solar Street Light PV Panel, Excellent efficiency based on innovative

Solar Street Light battery, Good safety, no risk of explosion

Solar Street Light battery, Large capacity, larger capacity than ordinary lead-acid batteries

Solar Street Light battery, Fit for use in regions of high altitude and wider range of temperatures

Solar Street Light battery, Excellent performance in capacity recovery

Battery Box Waterproof , IP 67, Antiseptic

Solar Street Light Controller, 12V/24V automatic identify or user-defined working voltage

Solar Street Light Controller, Gel, Sealed, Flooded and user-defined battery type option

Solar Street Light Pole, Precision cutting make sure every parts mated perfectly, very easy for you to install.

Solar Street Light Pole, New powder paniting methods make sure the surface more smooth, the color can be done as you like.

Solar Street Light Pole, Arm diameter:48&60mm

Parameters

Item		TL-5401	TL-5401	TL-5401	TL-5401
Light Style		Split	Split	Split	Split
POWER		60W	80W	100W	120W
	Flux	8100~9900 lm	10800~13200 lm	13500~16500 lm	16200~19800 lm
LED	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	60W	80W	100W	120W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Largest Wattage	180W monocrystalline silicon	240W monocrystalline silicon	300W monocrystalline silicon	360W monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре	battery 1650WH	battery 2200WH		Lithium iron phosphate battery 3300WH
	Life			5-8years	5-8years
Control	Туре	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM	ChanPower MPPT / PWM
	Charge /	valid for 6 hours	valid for 6 hours	valid for 6 hours	valid for 6 hours
	time	of sunshine	of sunshine	of sunshine	of sunshine
	Discharg e / time	Power48hrs,Full	Power48hrs,Full	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time			12hrs every day 3-5 rainning days	
	Normal Setting	Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4	4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	hours,X% Power Light 2nd 4	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light	Materials	Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance	Height 6-10M / Distance10-25M	0	Height 8-12M / Distance20-35M	Height 8-12M / Distance20-35M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
	Туре	m]	m]	Cone [Ø60mm/Ø180m m]	Cone [Ø60mm/Ø180m m]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating
D-1-	Length	6-10M	6-10M	8-12M	8-12M
Pole					

Thicknes s	2.5MM	2.5MM	3.0MM	3.0MM
Weight	35-45kg	35-45kg	40-50kg	40-50kg
Flange	250*250mm	250*250mm	300*300mm	300*300mm
Anchor Bolt	2kg	2kg	3kg	3kg

FAQ

- Q: What about the delivery date?
- A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.
- Q: Do you have any MOQ limit for led light order?
- A: for solar street light controller, 1pc for sample checking is available
- Q: How to choose the system Voltage 12V /24V ?
- A: Chanpower could design the system for you. Usually 12V system for 15W-40W LED lamp, 24V system for 50-150W LED lamp.
- Q: How do you ship the goods and how long does it take to arrive?
- A: Accessory sample shipped by DHL, UPS, FedEx ,TNT etc. It usually takes 3-5 days to arrive. Airline and sea shipping also optional.
- Q: What is your Warranty Policy?
- A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.
- Q: Can I have a sample order for led light?
- A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.
- Q: How do you ship the goods and how long does it take to arrive?
- A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.
- Q: How to proceed an order for solar led street light?
- A: Firstly,let us know your requirements or application.
- Secondly, Chanpower quote according to your requirements or our suggestions.
- Thirdly, customer confirms the details and places deposit for formal order.
- Fourthly, Chanpower arrange the production.

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C