



40 Watt CREE Chip All In One Solar Street Light Flux 5400lm Color Temp 4000K

Basic Information

Packaging Details:

Place of Origin: Shenzhen China
Brand Name: Chanpower
Certification: CE FCC ROHS
Model Number: TL-1403
Minimum Order Quantity: 500
Price: negotiable

• Delivery Time: 30~35 work days

Carton

• Payment Terms: L/C, T/T

Supply Ability: 2000 sets per month



Product Specification

• PV: 120W

• Battery: 1100ah LiFePO4

LED Fixture: 40watt
Color Temp: 4000K
Flux: 5400lm
Application: Street, Park

• Highlight: solar powered road lights

Product Description

Solar Street Light 40watt CREE Chip Flux 5400lm, Color Temp 4000K

Feature

Chanpower Manufactured according to international quality management system(ISO9001)

Solar Street Light LED Fixture with anti-reflective coating improving light absorption and reduces surface dust

High salt mist and ammonia resistance of LED fixture

Solar Street Light PV Panel, Superior Aluminium alloy material, radiating function is more efficient, make sure long lifespan

Solar Street Light PV Panel, Strong frame, passing mechanical load test of 5400pa, instead of the normal 2400pa.

Solar Street Light battery, Environmentally friendly, no heavy metals and rare metals, no poisons and no pollution, in line with RoHS environmental protection regulations

Solar Street Light battery, Light weight, the volume of the battery in the same capacity is 2/3 of the volume of the lead-acid battery, and the weight is 1/3 of the lead-acid battery.

Solar Street Light battery, Echo-friendly: No Cadmium. No leaking

Solar Street Light battery, Working temperature: -0 to +60 centigrade

Battery Box Heat protection

Solar Street Light Controller, Gel, Sealed, Flooded and user-defined battery type option

Solar Street Light Controller, New SOC method of calculating accurately displays the available battery capacity

Solar Street Light Controller, Support firmware upgrade

Solar Street Light Controller, Fully encapsulated PCB, IP67 protection

Solar Street Light Pole, Hot dip galvanizing (HDG) process make sure 10 years rusty and 20 years lifepan.

Solar Street Light Pole, Thickness: 2.75mm, 3mm



Parameters

Item		TL-1403-40	TL-1403-60	TL-1403-80	TL-1403-100
Light Style		Split	Split	Split	Split
POWER		40W	60W	80W	100W
LED	Flux	5400~6600 lm	8100~9900 lm	10800~13200 lm	13500~16500 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	60W	80W	100W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Largest Wattage	120W monocrystalline silicon	180W monocrystalline silicon	240W monocrystalline silicon	300W monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре	Lithium iron phosphate battery 1100WH	Lithium iron phosphate battery 1650WH		Lithium iron phosphate battery 2750WH
	Life	5-8years	5-8years	5-8years	5-8years
Control	Туре	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT
	Charge / time	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time			12hrs every day 3-5 rainning days	12hrs every day 3-5 rainning days
	Normal Setting		4 hours,X% Power Light 2nd	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4	hours,X% Power Light 2nd 4
Light	Materials	Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance	Height 5-10M / Distance10-25M	Height 5-10M / Distance10-25M		Height 5-10M / Distance15-30M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
Pole	Туре	m]	m]	Cone [Ø60mm/Ø140m m]	Cone [Ø60mm/Ø140m m]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Shee with Coating
	Length	5-10M	5-10M	5-10M	5-10M
	Thicknes s	2.5MM	2.5MM	2.5MM	2.5MM
	Weight	35-45kg	35-45kg	35-45kg	35-45kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Cround	2kg	2kg	2kg	2kg

FAQ

- Q: What is your Warranty Policy?
- A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.
- Q: Can I have a sample order for led light?
- A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.
- Q: What about the delivery date?
- A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.
- Q: Do you have any MOQ limit for led light order?
- A: for solar street light controller, 1pc for sample checking is available
- Q: How do you ship the goods and how long does it take to arrive?
- A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

Q: How to proceed an order for solar led street light?

A: Firstly,let us know your requirements or application.

Secondly, Chanpower quote according to your requirements or our suggestions.

Thirdly, customer confirms the details and places deposit for formal order.

Fourthly, Chanpower arrange the production.

Q: Can Chanpower use our my logo on the solar led light products?
A: Yes. Please inform us formally confirm the design before our production.

Q: Do you offer guarantee for the products?

A: Yes, Chanpower offer 3 years warranty to our products.

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD

17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C