



# Metal Material Solar Street Post Lights Cree Led Roadway Lighting 6 - 10 Meter

## **Basic Information**

Place of Origin: Shenzhen China
Brand Name: Chanpower
Certification: CE FCC ROHS
Model Number: TL-1601
Minimum Order Quantity: 500
Price: negotiable
Packaging Details: Carton

• Delivery Time: 30~35 work days

Payment Terms: L/C, T/T

• Supply Ability: 2000 sets per month



# **Product Specification**

• PV: Monocrystalline Silicon

Battery: LiFePO4Controller: MPPT/PWM

LED: 60WMaterials: MetalPole: 6-10 Meter

• Highlight: solar powered road lights

## **Product Description**

#### Metal Material Solar Street Post Lights Cree Led Roadway Lighting 6 - 10 Meter

#### Feature

Chanpower Manufactured according to international quality management system(ISO9001)

Solar Street Light LED Fixture with tempered glass, EVA lamination and weatherproof backsheet provide long-life and enhance cell performance

Solar Street Light LED Fixture cover, High Stength and High Transparent Toughened Glass

Solar Street Light PV Panel, Superior Aluminium alloy material, radiating function is more efficient, make sure long lifespan

Solar Street Light PV Panel, beautifully plate design, Highly optimized for general use

Solar Street Light battery, Built-in Chanpower designed BMS control circuit to ensure stable operation and high reliability

Solar Street Light battery, No memory effect, can often work under the condition of not filling out, charge and discharge at any time, no need to finish and recharge

Solar Street Light battery, Easy transportation with no leaking of battery

Solar Street Light battery, Real green and environmentally friendly batteries

Battery Box Life span: 20years

Solar Street Light Controller, Use MOSFET as electronic switch, without any mechanical switch

Solar Street Light Controller, Multiple load control modes, increase the flexibility of the load output

Solar Street Light Controller, Intelligent power mode, to maximize the lighting time.

Solar Street Light Controller, Advanced constant current control technology to ensure smooth and stable output current, reduce light failure, extend LED life.

#### **Parameters**

Item		TL-1601-40	TL-1601-60	TL-1601-80	TL-1601-100
Light Style		Split	Split	Split	Split
POWER		40W	60W	80W	100W
LED	Flux	5400~6600 lm	8100~9900 lm	10800~13200 lm	13500~16500 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	60W	80W	100W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Lorgost	120W	180W	240W	300W
	Largest Wattage	silicon	monocrystalline silicon	monocrystalline silicon	monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре		Lithium iron phosphate battery 1650WH		Lithium iron phosphate battery 2750WH
	Life		5-8years	5-8years	5-8years
	Туре	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT
Control	Charge / time	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time		Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time		12hrs every day 3-5 rainning days	12hrs every day 3-5 rainning days	12hrs every day 3-5 rainning days
	Normal Setting	Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power	4 hours,X% Power Light 2nd	Power Light 1st 4 hours,X% Power Light 2nd 4	5 Time Save Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light	1	Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance		Height 5-10M / Distance10-25M	Height 5-10M / Distance15-30M	Height 5-10M / Distance15-30M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
	Туре	Cone [Ø60mm/Ø140m m]	m]	m]	Cone [Ø60mm/Ø140m m]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating

			5-10M	5-10M	5-10M
	Thicknes s	2.5MM	2.5MM	2.5MM	2.5MM
	Weight	35-45kg	35-45kg	35-45kg	35-45kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Ground Cage	2kg	2kg	2kg	2kg



Q: How do you ship the goods and how long does it take to arrive?

A: Accessory sample shipped by DHL, UPS, FedEx ,TNT etc. It usually takes 3-5 days to arrive. Airline and sea shipping also

Q: What is your Warranty Policy?

A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.

Q: Can I have a sample order for led light?

A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.

Q: What about the delivery date?

A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.

Q: Do you have any MOQ limit for led light order?

A: for solar street light controller, 1pc for sample checking is available

Q: How do you ship the goods and how long does it take to arrive?

A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

Q: How to proceed an order for solar led street light?

A: Firstly,let us know your requirements or application.

Secondly, Chanpower quote according to your requirements or our suggestions.

Thirdly, customer confirms the details and places deposit for formal order.

Fourthly, Chanpower arrange the production.

# SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C