



# LED Pathway All In One Solar Street Light Plate Design 13000lm Battery Lifespan

## **Basic Information**

Place of Origin: Shenzhen China
Brand Name: Chanpower
Certification: CE FCC ROHS
Model Number: TL-1901
Minimum Order Quantity: 500
Price: negotiable

Packaging Details: Carton

• Delivery Time: 30~35 work days

Payment Terms: L/C, T/T

Supply Ability: 2000 sets per month



# **Product Specification**

Solar Panel: Mono
Solar Battery: LiFePO4
Solar Charger: PWM/MPPT
LED: 40-100Watt
Materials LED: Aluminium
Pole: Metal Galvanized

Application: RoadHight: 6-10meter

• Highlight: solar powered road lights

## **Product Description**

#### LED Pathway All In One Solar Street Light Plate Design 13000lm Battery Lifespan

### **Feature**

Average distribution light lens, long pole distance, easy to get the acceptance requirements

Solar Street Light LED Fixture is easy to install and handle for various applications

Solar Street Light LED Fixture, Cree or bridgelux leds 3w/pc, big size chip and gold line, real 45mil, high lumen

Solar Street Light PV Panel, beautifully plate design, Highly optimized for general use

Solar Street Light PV Panel, with stand heavier snow load and higher wind-pressure.

Solar Street Light battery, High temperature performance, electric heating peak is twice that of LiNiCoMnO2 battery

Solar Street Light battery, Long service life, using cells with more than 2000 cycles, life expectancy of more than 5 years

Solar Street Light battery, Environmentally friendly, no heavy metals and rare metals, no poisons and no pollution, in line with RoHS environmental protection regulations

Solar Street Light battery, Light weight, the volume of the battery in the same capacity is 2/3 of the volume of the lead-acid battery, and the weight is 1/3 of the lead-acid battery.

Battery Box Waterproof , IP 67, Antiseptic

Solar Street Light Controller,12V/24V automatic identify or user-defined working voltage

Solar Street Light Controller, High efficient Series PWM charging, increase the battery lifetime and improve the solar system performance

Solar Street Light Controller, RF remote control settings, read, view data.

Solar Street Light Controller, Provides battery reverse protection, solar panel reverse protection, prevent battery discharging to solar panel at night, battery low-voltage protection, battery quit low-voltage protection, LED load short-circuit protection, LED load open-circuit protection, over-temperature protection, TVS anti-thunder protection etc.

#### **Parameters**

Item		TL-1901-40	TL-190160	TL-190180	TL-1901100
Light Style		Split	Split	Split	Split
POWER		40W	60W	80W	100W
LED	Flux	5400~6600 lm	8100~9900 lm	10800~13200 lm	13500~16500 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	60W	80W	100W
	Life		50000hrs	50000hrs	50000hrs
Solar Panels	vvallage	silicon	monocrystalline silicon	240W monocrystalline silicon	300W monocrystalline silicon
	Life		25years	25years	25years
Battery		phosphate battery 1100WH	battery 1650WH		Lithium iron phosphate battery 2750WH
	Life			5-8years	5-8years
Control	Туре	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT	ChanPower MPPT
	3		valid for 6 hours of sunshine	valid for 6 hours of sunshine	valid for 6 hours of sunshine
	Discharg e / time		Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time				12hrs every day 3-5 rainning days
	Setting	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]	Light 2nd 4 hours, X% Power Light 3rd 4 hoursr]
Light		Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	and Distance	Distance10-25M	Distance10-25M		Height 5-10M / Distance15-30M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM

		Cone	Cone	Cone	Cone
Pole	Туре	[Ø60mm/Ø140m	[Ø60mm/Ø140m	[Ø60mm/Ø140m	[Ø60mm/Ø140m
		m]	m]	m]	m]
		Galvanized	Galvanized	Galvanized	Galvanized Sheet with Coating
		Sheet with	Sheet with	Sheet with	
		Coating	Coating	Coating	
			5-10M	5-10M	5-10M
	Thicknes	2 51/11/1	2.5MM	2.5MM	2.5MM
	s	2.5111111			
	Weight	35-45kg	35-45kg	35-45kg	35-45kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Ground	2kg	2kg	2kg	2kg
	Cage				



Q: Can Chanpower use our my logo on the solar led light products?

A: Yes. Please inform us formally confirm the design before our production.

Q: Do you offer guarantee for the products?

A: Yes, Chanpower offer 3 years warranty to our products.

Q:How to deal with the faulty?

A: Firstly, Please send us some pictures or videos of the faulty item for our analyzation. Our products are produced in strict quality control system and the defective rate will be less than 0.2%.

Secondly, during the guarantee period, Chanpower will send new parts with new order for defective products and Chanpower will assess if it's necessary to return the faulty item, Chanpower can discuss the solution including recall according to real situation.

Q:Can I Get A Lower Price If I Order Large Quantities?

A:Different Order Quantity Different Price, In Addition Any Customized Service Is Available According To Target Price.

Q:Can I Get The Pre-Production solar street controller Sample?

A:Yes, Pre-Production solar street controller Sample Is Available.

Q: When You Ship My Order?

A:Standard Lead Time Base On Order Details, Any Urgent Please Tell Us Freely, Then Help You.

Q:How About The Quality Guarantee Period?

A:3 Years Warranty And Free Spare Parts Service

Q: How Can You Guarantee The Production Quality?

A: Strict QA System, IQC/PQC/FQC With Internal Inspection, Any 3Rd Party Inspection Is welcome Too.

Q: What are LEDs and how do they work?

A: LEDs or Light Emitting Diodes are a form of semi-conductor. They do not have the gas filled chambers or lighting filaments associated with conventional lamp types. When you pass a current through the LED, it results in the required outcome of light or electroluminescence. Chanpower LEDs present many advantages over conventional light sources including lower energy consumption, longer lifetime, improved robustness, smaller size, faster switching and greater durability and reliability.

## SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



e solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C