

Long Pole Distance All In One Solar Street Light, LED Solar Area Lights

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

Charge Controller:

. LED Materials:

• PV: • Battery:

• LED:

• Pole:

Color:

Monocrystalline Silicon Li-ion MPPT 40W~100W Aluminium 5~10 Meter Optional

Shenzhen China

CE FCC ROHS

TL-2101 / TL-2102

30~35 work days

2000 sets per month

Chanpower

negotiable

Carton

500

- Application:
- Highlight:
- Parking, Street
- solar powered road lights

Long Pole Distance All In One Solar Street Light, LED Solar Area Lights

Feature

- Average distribution light lens, long pole distance, easy to get the acceptance requirements
- Solar Street Light LED Fixture is easy to install and handle for various applications
- Solar Street Light LED Fixture surface with Polyester Substance
- Solar Street Light PV Panel, beautifully plate design , Highly optimized for general use Solar Street Light PV Panel, Glass light distribution, no PC diffuser, once distributing light makes sure only less loss of ray Solar Street Light battery, Good safety, no risk of explosion
- Solar Street Light battery, Large capacity, larger capacity than ordinary lead-acid batteries
- Solar Street Light battery, Extremely low internal resistance and self-discharge rate
- Solar Street Light battery, Long life design
- Battery Box Pressure resistant, Good ventilation, Patented design
- Solar Street Light Controller, 12V/24V automatic identify or user-defined working voltage

Solar Street Light Controller, High efficient Series PWM charging, increase the battery lifetime and improve the solar system performance

Solar Street Light Controller, IR and MW sensor optional

Solar Street Light Controller, Charging battery even in 0 Voltage, activate aromatically.

- Solar Street Light Pole, Q235A superior quality steel for Poles
- Solar Street Light Pole, Arm diameter:48&60mm

Parameters

Item		TL-2101/02-40	TL-2101/02-60	TL-2101/02-80	TL-2101/02-100
Light Style			Split		Split
POWER		40W	60W	80W	100W
LED	Flux	5400~6600 lm	8100~9900 lm	10800~13200 lm	13500~16500 lm
	Color Temp	4000~6000K	4000~6000K	4000~6000K	4000~6000K
	Brand	CREE	CREE	CREE	CREE
	Max Power	40W	60W	80W	100W
	Life	50000hrs	50000hrs	50000hrs	50000hrs
Solar Panels	Largest Wattage		180W monocrystalline silicon	monocrystalline	300W monocrystalline silicon
	Life	25years	25years	25years	25years
Battery	Туре		Lithium iron phosphate battery 1650WH	Lithium iron phosphate	Lithium iron phosphate battery 2750WH
	Life		5-8years	5-8years	5-8years
	Туре	MPPT / PWM	MPPT / PWM	MPPT / PWM	MPPT / PWM
	Charge / time		valid for 6 hours of sunshine		valid for 6 hours of sunshine
	Discharg e / time	Power48hrs,Full Power 24hrs	Power 24hrs	Power48hrs,Full Power 24hrs	Half Power48hrs,Full Power 24hrs
	Lighting Time	12hrs every day 3-5 rainning days	12hrs every day 3-5 rainning days	3-5 rainning days	12hrs every day 3-5 rainning days
	Normal Setting	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power	4 hours,X% Power Light 2nd	Setting,[eg. X% Power Light 1st 4 hours,X% Power Light 2nd 4 hours, X% Power Light 3rd 4	hours,X% Power Light 2nd 4
Light	Materials	Aluminium	Aluminium	Aluminium	Aluminium
Fixture	Style	Selectable	Selectable	Selectable	Selectable
Installatio n	Height and Distance		Height 5-10M / Distance10-25M		Height 5-10M / Distance15-30M
	Installatio n Hole	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM	Diameter:40- 75MM
	Туре	Cone [Ø60mm/Ø140m m]	m]	m]	Cone [Ø60mm/Ø140m m]
	Material	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating	Galvanized Sheet with Coating

			5-10M	5-10M	5-10M
	Thicknes s	2.5MM	2.5MM	2.5MM	2.5MM
	Weight	35-45kg	35-45kg	35-45kg	35-45kg
	Flange	250*250mm	250*250mm	250*250mm	250*250mm
	Ground Cage	2kg	2kg	2kg	2kg

FAQ

Q: Are you a factory or a trading company?

A: Chanpower is the factory with high production capacity and product range of solar products in China.

Q: How to choose the system Voltage 12V /24V ?

A: Chanpower could design the system for you. Usually 12V system for 15W-40W LED lamp , 24V system for 50-150W LED lamp.

Q: How do you ship the goods and how long does it take to arrive? A: Accessory sample shipped by DHL, UPS, FedEx ,TNT etc. It usually takes 3-5 days to arrive. Airline and sea shipping also optional .

Q: What is your Warranty Policy?

A: Chanpower offer 3 years warranty for the entire system and replace with new ones for free in case of quality problems.

Q: Can I have a sample order for led light?

A: Yes, Chanpower welcome sample order to test and check quality. Split style solar street lights is suitable for project according to clients' requirement, need more time for confirm.

Q: What about the delivery date?

A: Sample needs 3-5 days, mass production time needs 1-4 weeks for order quantity more than one container.

Q: Do you have any MOQ limit for led light order?

- A: for solar street light controller, 1pc for sample checking is available
- Q: How do you ship the goods and how long does it take to arrive?

A: Chanpower usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. By sea or by air optional.

Q: How to proceed an order for solar led street light?

A: Firstly,let us know your requirements or application. Secondly,Chanpower quote according to your requirements or our suggestions. Thirdly,customer confirms the details and places deposit for formal order. Fourthly,Chanpower arrange the production.

Q: Can Chanpower use our my logo on the solar led light products?

A: Yes. Please inform us formally confirm the design before our production.

Q: Do you offer guarantee for the products?

A: Yes, Chanpower offer 3 years warranty to our products.

