



Aluminum High Power 100W Bi Color LED Photography Studio Light 120° Wide Beam Angle

Basic Information

Place of Origin: ChinaBrand Name: LS

Certification: CE, RoHSModel Number: P-1380ASVL

• Minimum Order Quantity: 10

Price: Negotiation
Packaging Details: 2pcs per cartons
Delivery Time: 7 work days

Payment Terms: T/T

Supply Ability: 500pcs per month



Product Specification

Product Name: Bi Color LED Photography Studio Light

Model No.: P-1380ASVLMaterial: Alluminum Alloy

• Power: 100W

• Color Termperature: 3200~5900K

• CRI: ≥95

Voltage: 100-240V AC, 15VDC
 Beam Angle: 120° Wide Beam
 Highlight: movie studio lights



Product Description

Aluminum High Power 100W Bi Color LED Photography Studio Light 120° Wide Beam Angle

Standard set Includied

- 1 piece of P-1380ASVL light
- 1 piece of adapter and power cord
- 1 set 4-leaves barndoor
- 1 piece of DMX cable

Optional accessories:

Honeycomb Grid Alluminum box for 2 pieces of lights Alluminum box for 3 pieces of lights Light stand Carrying bag for two pcs of lights

Product Show





Product Characteristics

- Dimming 10-100%, flicker-free.
- Color temperature can be adjustable from 3200K all the way to 5900K. It produces soft, bright light ray with standard color temperature daylight or tungsten.
- High CRI above 95.
- It is heat free and remains consistent even as the battery voltage does down...
- It is suitable for broadcast studio and film shooting.
- Runs on AC adapter or battery.

Product Specifications

Model	P-1380ASVL	
LED Type	SMD	
LED quantity	1200 PCS	
Power	100W	
Color termperature	3200~5900K	
Illuminance	2458Lux/m , 670Lux/2m	
Weight	4.8KG	
Beam Angle	120° wide beam	
	1	

|--|

Distance	Illuminance	
	3200K	5600K
1M	2458Lux	2458Lux
2M	680Lux	750Lux

Cautions:

- 1. It is no need to replace the LED bulbs in normal use. Please do not disassemble the light or solder the LED bulbs by the non-professionals.
- 2. Please do take off the batteries when in storage.
- 3. Please do not block the louvers,or it may seriously influence LEDs' effect and lifetime.
- 4. The charger adapter is used for battery charging only. Please do not use on the light directly.
- 5. Please do discharge and recharge the battery at least once for every month if it is not in use.
- 6. It is not allowed to drop or impact the light to avoid fire.
- 7. It is not allowed to short circuit the battery, or it may seriously damage the battery or cause a
- 8. It is not allowed to throw the battery into fire.

Warranty:

The LED light is guaranteed for 1Year.

About shipment

We can arrange the shipment under FOB with your shiping agent or our shiping agent.

We can also provide shipment service under CNF, CIF The nearby shiping port in Ningbo.

We can also send goods to other ports if necessary.

Airshipment can also be arranged usually in Shanghai airport.

About payment

Bank Telegraphic Transfer T/T, West Union.

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C