



## WW/NW/CW Indoor LED Strip Lights Ceiling Stick Able With 3 Years Warranty

### Our Product Introduction

#### Basic Information

- Place of Origin: Shenzhen China
- Brand Name: TL
- Certification: CE RoHS ETL UL
- Model Number: TL-FW28CE-IN98-CV80-10-24V-CCT
- Minimum Order Quantity: 1000M
- Price: Negotiable
- Packaging Details: Cartons
- Delivery Time: 2-3 weeks
- Payment Terms: T/T
- Supply Ability: 30000M per month



#### Product Specification

- LED SMD: 2835 Chips
- Color: 2200-6500K
- Luminous Efficiency: 125~135lm/w
- Voltage: 24VDC
- Wattage: 19.6W/M
- CRI: 80
- Type: Flex LED Strips
- Lamp Body Material: Copper
- Highlight: **external led strip lights**

## Product Description

SMD2835 LEDs Indoor LED Strip Lights 71.4mm Cutting length 24VDC CRI80 120lm per watt

### SMD2835

- 1, High luminous Efficiency 120~130lm/w
- 2, 98LEDs per meter, 7LEDs per cutting
- 3, 24DCV
- 4, Warranty 3 years
- 5, Beam angle 120°
- 6, 2 layer PCB/1+2OZ copper 8mm width
- 7, CRI≥80, lifetime 30000h
- 8, CCT/X.Y: 2300k 2700k 3000k 4000k 5000k 6000k

### 1, Features

High quality flexible PCB strip with ETL, RoHS and CE certified  
 Use 2835 SMD LED as light source with high brightness and large view angle  
 Environment friendly, no UV, noinfrared, no radiation  
 Use high quality LED  
 7pcs LED/cutting section

Item	Unit	Data		Item	Unit	Data
LED type	/	SMD 2835		LED quantity/m	PCS	98
LED brand	/	Epistar or equivalent Sanan		LED power dissipation/m	W	19.62
Beam angle	261/2	120		Strip power dissipation/m	W	21.8
PCB type	type	2 layer PCB/1+2oz copper 10mm		Luminous flux±10%	lm/m	3000
Length	M	5		Efficacy	lm/w	140
Protection degree	IP	IP20		Operating Voltage	VDC	24
Tape	/	9495 200MP		Operating current/m	A	0.91
Color	/	WW/NW/CW		Ta(ambient temperature)		-20 ~60
CRI	Ra	≥90		Tc(surface temperature)		Max. 67
CCT	2700k	27S(2645-2805K) X=0.459 Y=0.412	120lm/w	Heatsink	[c /m]	654
	3000k	29S(2854-3026K) X=0.44 Y=0.403	120lm/w	Warranty period	year	3
	4000k	41S(3897-4223K) X=0.38 Y=0.38	130lm/w	Life time	H	30000
	5000k	50S(4900-5300K) X=0.346 Y=0.359	130lm/w			

### 2, Layout

---

### 3, Outline drawing

---

### 4, Connection Diagram

---

### 5, Package

---



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



[solarpanelstreetlight.com](http://solarpanelstreetlight.com)

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C