




## High Brightness Color Changing LED Strip CRI90 50000h Long Work Life

### Our Product Introduction

#### Basic Information

- Place of Origin: Shenzhen China
- Brand Name: TL
- Certification: CE RoHS ETL UL
- Model Number: TL-FW28HE-IN126-CV90-10-24V-CCT
- Minimum Order Quantity: 1000M
- Price: Negotiable
- Packaging Details: Cartons
- Delivery Time: 2 to 3 weeks
- Payment Terms: T/T
- Supply Ability: 30000M per month



#### Product Specification

- LED SMD: SMD2835
- Color: 2200-4000K
- Luminous Efficiency: 150~160lm/w
- Voltage: 24VDC
- Wattage: 25W/M
- CRI: 90
- Working Lifetime(hour): 50000h
- Pcb Color: Copper Color
- Highlight: exterior led tape light

for more products please visit us on [solarpanelstreetlight.com](http://solarpanelstreetlight.com)

## Product Description

126pcs 2835LEDs 55.5mm Cutting length Indoor LED Strip Lights 24VDC CRI80 160lm per watt

### SMD2835

- 1, High luminous Efficiency 150~160lm/w
- 2, 126LEDs per meter, 7LEDs per cutting
- 3, 24DCV
- 4, Warranty 3 years
- 5, Beam angle 120°
- 6, 2 layer PCB/1+2OZ copper 10mm width
- 7, CRI≥90, lifetime 50000h
- 8, CCT/X.Y: 2200k 2700k 3000k 4000k

### 1, Features

- High quality flexible PCB strip with UL ETL RoHS and CE certified
- Use 2835 SMD LED as light source with high brightness and large view angle
- Environment friendly, no UV, no infrared, no radiation
- Use high quality LED
- 7pcs LED/cutting section

Item	Unit	Data		Item	Unit	Data
LED type	/	SMD 2835		LED quantity/m	PCS	126
LED brand	/	Epistar or equivalent Sanan		LED power dissipation/m	W	23.3
Beam angle	2θ/2	120		Strip power dissipation/m	W	25.9
PCB type	type	2 layer PCB/1+2oz copper 10mm		Luminous flux±10%	lm/m	3500
Length	M	5		Efficacy	lm/w	155
Protection degree	IP	IP20		Operating Voltage	VDC	24
Tape	/	TIA806FG		Operating current/m	A	1.08
Color	/	WW/NW/CW		Ta(ambient temperature)		-20 ~60
CRI	Ra	≥90		Tc(surface temperature)		Max. 67
CCT	2700k	27S(2645-2805K) X=0.459 Y=0.412	130lm/w	Heatsink	[c /m]	777
	3000k	29S(2854-3026K) X=0.44 Y=0.403	130lm/w	Warranty period	year	3
	4000k	41S(3897-4223K) X=0.38 Y=0.38	150lm/w	Life time	H	30000
	5000k	50S(4900-5300K) X=0.346 Y=0.359	160lm/w			

### 2, Layout

---

### 3, Outline drawing

---

### 4, Connection Diagram

---



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



[solarpanelstreetlight.com](http://solarpanelstreetlight.com)

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C