



24vDC CRI90 Indoor LED Strip Lights 130lm / Watt SMD 2835 128 LEDs Per Meter

Our Product Introduction

Basic Information

- Place of Origin: Shenzhen China
- Brand Name: TL
- Certification: CE RoHS ETL UL
- Model Number: TL-FW28HE-IN128-CV90-10-24V-CCT
- Minimum Order Quantity: 1000M
- Price: Negotiable
- Packaging Details: Carton Box
- Delivery Time: Two to Three weeks
- Payment Terms: T/T
- Supply Ability: 30000M per month



Product Specification

- LED SMD: SMD 2835
- Color: 2200k To 4000k
- Luminous Efficiency: 130~135lm/w
- Voltage: 24vDC
- Wattage: 23W Per Meter
- CRI: 90
- Working Lifetime(hour): 50000h
- Emitting Color: Red/ Yellow/ Blue/ Green/ White/ Warm White/ RGB
- Highlight: exterior led tape light



Product Description

128LEDs Per Meter Inddor 8LEDs Cutting LED Strip Lights 24vDC CRI90 130lm per watt

SMD2835

- 1, High luminous Efficiency 130~135lm/w
- 2, 128LEDs per meter, 8LEDs per cutting
- 3, 24DCV
- 4, Warranty 3 years
- 5, Beam angle 120°
- 6, 2 layer PCB/1+2OZ copper 10mm width
- 7, CRI≥90, lifetime 50000h
- 8, CCT/X.Y: 2200k 2500k 2700k 3000k 4000k

1, Features

High quality flexible PCB strip with ETL, RoHS and CE certified
 Use 2835 SMD LED as light source with high brightness and large vier angle
 Environment friendly, no UV, noinfrared, no radiation
 Use high quality LED
 8pce LED/cutting section

Item	Unit	Data		Item	Unit	Data
LED type	/	SMD 2835		LED quantity/m	PCS	128
LED brand	/	Epistar or equivalent Sanan		LED power dissipation/m	W	22.5
Beam angle	261/2	120		Strip power dissipation/m	W	23
PCB type	type	2 layer PCB/1+2oz copper 10mm		Luminous flux±10%	lm/m	3300
Length	M	3		Efficacy	lm/w	135
Protection degree	IP	IP20		Operating Voltage	VDC	24
Tape	/	TIA806FG		Operating current/m	A	1.05
Color	/	WW/NW		Ta(ambient temperature)		-20 ~60
CRI	Ra	≥90		Tc(surface temperature)		Max. 67
CCT	2700k	27S(2645-2805K) X=0.459 Y=0.412	125lm/w	Heatsink	[c /m]	750
	3000k	29S(2854-3026K) X=0.44 Y=0.403	130lm/w	Warranty period	year	3
	4000k	41S(3897-4223K) X=0.38 Y=0.38	135lm/w	Life time	H	50000
	5000k	50S(4900-5300K) X=0.346 Y=0.359	135lm/w			

2, Layout

3, Outline drawing

4, Connection Diagram

5, Package



Beijing Silk Road Enterprise Management Services Co.,LTD



17733330123



miclecleanmo@gmail.com



solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C