

# CRI90 Outdoor LED Strip Lights, 130Im Exterior LED Tape Light Large View Angle

## **Basic Information**

- Place of Origin:
- Shenzhen China ΤL • Brand Name:

ETL CE RoHS UL

Negotiable

Cartons

2-3 weeks

30000M per month

TL-FW28HE-IN70-CV90-8-24V-30K

- Certification:
- Model Number:
- Minimum Order Quantity: 1000M
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



### **Product Specification**

• LED SMD:	2835 LEDs
Color:	2000 To 6000K
<ul> <li>Luminous Efficiency:</li> </ul>	115-155lm/w
• Voltage:	24VDC
• Wattage:	16W Per Meter
• CRI:	90
• Working Temperature( ):	-20~65
<ul> <li>Working Lifetime(hour):</li> </ul>	30000h
Highlight:	external led strip lights

Our Product Introduction

#### **Product Description**

70pcs CRI90 Outdoor LED Strip Lights 140Im Large Vier Angle Exterior LED Tape Light

SMD2835

1,High luminous Efficiency 115~155lm/w

2,70LEDs per meter, 7LEDs per cutting

- 3,24DCV Warranty 3 years
- 4,Beam angle 120° 2 layer PCB/1+1OZ copper 8mm width
- 5,CRI≥90, lifetime 30000h

6,CCT/X.Y: 2200k 2700k 3000k 4000k

1, Features

High quality flexible PCB strip with ETL UL RoHS and CE certified Use 2835 SMD LED as light source with high brightness and large vier angle Environment friendly, no UV, noinfrared, no radiation Use high qualily LED 7pce LED/cutting section

Item	Unit	Data		Item	Unit	Data
LED type	/	SMD 2835		LED quantity/m	PCS	70
LED brand	/	Epistar or equivalent Sanan 2 120		LED power dissipation/m	W	15.1
Beam angle	201/2			Strip power dissipation/m	W	16.5
PCB type	type	2 layer PCB/1+1oz copper 8mm		Luminous flux±10%	lm/m	2210
Length	М	5		Efficacy	lm/w	130
Protection degree	IP	IP20		Operating Voltage	VDC	24
Tape	/	3M 9495 200MP		Operating current/m	A	0.7
Color	/	WW/NW           ≥90		Ta(ambient temperature)		-20 ~60
CRI	Ra			Tc(surface temperature)		Max. 67
	2000k	27S(2645-2805K) X=0.459 Y=0.412	115lm/w	Heatsink	[c /m]	504
ССТ	3000k	29S(2854-3026K) X=0.44 Y=0.403	125lm/w	Warranty period	year	3
	4000k	41S(3897-4223K) X=0.38 Y=0.38	135lm/w	Life time	н	30000
	6000k	50S(4900-5300K) X=0.346 Y=0.359	155lm/w			

#### 2, Layout

3, Outline drawing

4, Connection Diagram

5, Package

SOLAR SLIGHT Beijing Silk Road Enterprise Management Services Co., LTD

I7733330123 miclecleanmo@gmail.com

© solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C