



IP66 Solar LED Flood Lights Modular AC100 - 240V 50000 Hours Excellent Heat Conductivity

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: JULANG
- Certification: CE/EMC/LVD
- Model Number: PHFL200WRD
- Minimum Order Quantity: 1pc For Sample
- Price: USD68-USD170
- Packaging Details: each in a box, 4pcs per carton
- Delivery Time: 15-25 WORKING DAYS
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 3000PCS PER WEEK



Product Specification

- Light Source: LED,epistar/bridgelux Chip/bridgelux
- Input Voltage(v): AC100-240V,110-240,AC85-265V/12V/24V
- Item Type: Flood Lights
- Lamp Body Material: Aluminum,Aluminum/ASA,Alumimnum+glass
- Application: Sports
Stadiums,LANDSCAPE,Garden,Square,Building
- Color Temperature(cct): Warm White,Pure White,2700-6500K
- Product Name: Flood Led Light,IP65 Outdoor Usage Remote Control 10W RGB LED Flood Lights,waterproof Ip65 Outdoor Smd Solar Led Flood Light Price,Stadium White Square LED Flood Light 10W 20W 100W 200W,garden Projector Lamp 12v Smd 200w Rechargeble Solar Led Flood Light
- Warranty: 3 Years,2 Years,5 Years,3 Years/50000 Hours
- Power: 100W,50W/100W/150W/200W/250W/300W,60W,10W 30W 50W 100W

Product Description

IP66 Solar LED Flood Lights Modular AC100 - 240V 50000 Hours Excellent Heat Conductivity

Product Feature:

Excellent heat conductivity.

The transmittance is up to 92%.

Use toughened glass, high temperature resistance.

The surface of the radiator is treated with anodic oxidation.

Simple installation, easy to remove, wide range of application.

Efficient heat sink: use of die-casting cold forging technology, large cooling area, good cooling effect.

Shell with high-pressure die-casting aluminum, solid and stable structure, strong impact resistance, strong pit shock, shell surface paint treatment, anti-oxidation, anti-salt spray, anti-corrosion, anti-rust.

Use High luminous SMD3030 light source, with higher luminous efficiency, can get about 135-150lm/w, after we test, less light failure, energy saving and better illumination effect, high stability, longer life-span.

Resist Lightening surge voltage 4KV to 8KV.

PRODUCT PARAMETERS:

Product name :	High power LED High Bay Light
Power :	200w
Light source :	SMD3030 Lumileds chips
Luminous efficiency :	135 lm/w
Beam angle :	25°/60°/90°/120° (by different lampshade)
Color temperature:	3000K/4000K/5000K/5700K/6500K
CRI:	>70 or >80
Driver :	Meanwell Driver
Input :	AC100-305V
Housing color available :	Normally Black
IP rating :	IP65
PF:	0.95

Item name: LED flood light with explosionproof

Input Voltage: AC 90V-285V

Rate Wattage: 200w

Lamp Luminous Flux(lm): 28000lm

CRI(RA)>80

Explosion proof: yes

Working Lifetime: 50000hours

Driver brand: driver

Warranty time: 3-5 years

Lamp body materials: aluminium alloy

LED souce: SMD3030

Color Temperature: 4000k, 6000k, 6500k

Beam Angle: 90° or 120°

Body Material: aluminium alloy + Lens cover

Water proof standard: IP65/67

Packing: each in a box

Applications: gym, industrial zone, commercial building, airport, sport playground, train station.

Benefit: long lifetime, high lumen, low maintainness cost, good outlook

SOLAR LIGHT Beijing Silk Road Enterprise Management Services Co.,LTD

☎ 17733330123

✉ miclecleanmo@gmail.com

🌐 solarpanelstreetlight.com

No 41, Dongsihuan Zhong Road, Chaoyang District, Beijing, 100025, P.R.C