

AC220V 5W 7W 9W LED Recessed Downlight / Energy Saving Round LED Down Lamp

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: One Carton
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T, Paypal, Western Union

China ADO

CE ROHS

Negotiation

3-7 work days

20 Pieces One Carton

10,000 pcs per day

AD-DL-12W-D

Supply Ability:



Product Specification

Power: 12W
Dimmable: Yes
CCT: 4000K
LED Chip: SMD2835
CRI: 80RA
Voltage: AC220V
Highlight: led down lamp



More Images





4000K Energy saving round led lamp 5w/7w/9w/12w/15w/18w/24w led recessed downlight

1. LED Down Light Specification:

| Light Source | LED |
|-------------------------|---------------------------------------|
| Warranty(Years): | 3 |
| Input Voltage(V): | AC100-240V |
| Lamp Luminous Flux(Im): | 500 |
| CRI (Ra>): | 80 |
| Working Lifetime(Hour): | 50000 |
| Lamp Body Material: | PC+Aluminum |
| IP Rating: | IP44 |
| Certification: | C-tick, CCC, CE, EMC, RoHS, SAA, SASO |
| Model Number: | AD-TDSMD-5W |
| Place of Origin: | Guangdong, China (Mainland) |
| Brand Name: | ADO |
| Application: | office |
| LED Light Source: | SMD2835 |
| OEM/ODM: | is Available |
| Dimmable: | is Available |
| Beam Angle: | 120degree |
| Chip Brand: | Epistar Bridgelux Sanan |
| Power: | 5w/7w/9w/12w/15w/18w/24w |
| Material: | Plastic coated Aluminum |
| CCT: | 3000K 4000K 6000K |
| Cover: | frosted Milky |
| PF: | >0.9 |
| Item Type: | Downlights |

2. LED Down Light Advantages:

- 1. Ultra-thin Thread design, 6063 aluminum die-casting heat sink
- 2. Uniform Lighting, luminous transmission rate>85%
- 3. 2 or 3 Spring buckle to firm secure, max adjustable angle 150 degree
- 4. Brand LED Samsung / SMD, high lumen 100LM/W, CRI>95Ra, 10W-40W for option
- 5. Extruded section 6063 aluminum, adopt external isolated constant current driver, flick free driver: Osram / / Tridonic
- 6. Wire Diameter: 4.5mm steady secure, DC interface diameter: 11mm, quickly connected, easily disassemble
- 7. High Brightness 120 degree beam angle, flicker free, UGR<19, 0-10V / DALI dimming Function, CE RoHs, 5 years warranty

3. Feature:

- 1.80%~90% energy saving than incandescent lamp,
- 2. Anti-shock, anti-moisture.
- 3. Advanced constant current driver.
- 4. No flickering,No RF interference,No UV radiation,
- 5. Body termerature less than 53 °C,
- 6. Easy installation, maintenance free.
- 7. Professional thermal management.
- 8. Great heat dissipation due to unique structural design.

4. Applications:

- 1. Store, plaza, supermarket, mall, warehouse lighting.
- 2. School, office, meeting room, hospital, residential lighting.
- 3. Restaurant, hotel bedroom, dining room, bar, hall, lobby lighting.
- 4. Show room, counter, display window, museum lighting, etc.



