

Non Dimmable Led Recessed Downlight Ultra - Thin Thread Design Steady Secure



Product Specification

٠	Item Type:
٠	Power:
•	CRI:

Downlights 17W

3000K/6000K

led down lamp

> 80 100°

- Beam Angle:
- Color Temperature:
- Application: Residential
- Highlight:
- Be
 Co
 Ap
 Hig

Product Description

Non Dimmable Led Recessed Downlight Ultra - Thin Thread Design Steady Secure

1. LED Down Light Specification:

LED Downlight Specifications		
Model	DL-L6	
Normal Voltage	AC 220-240V	
Power	17W	
Cut Hole (mm)	78	
Diameter φ(mm)	ØD174*69	
Lumens	1360lm	
LED chip	CREE COB	
CRI	>90Ra or >80Ra	
ССТ	3000K/6000K	
Beam Angle	100°	
Color	white	
Housing	Dia-cast Aluminum	
LED Driver	High PFC0.95 LED constant current driver	
Lifespan	50000hours	
Certificate	CE,ROHS	
Warranty	3 years	

3. LED Down Light Advantages:

1. Ultra-thin Thread design,

- 2. Uniform Lighting, luminous transmission rate>85%
- 3. 2 or 3 Spring buckle to firm secure, max adjustable angle 150 degree
- 4. Brand LED Samsung / Philips SMD, high lumen 100LM/W, CRI>80Ra
- 5. Extruded section adopt external isolated constant current driver, flick free driver: Osram / Philips / Tridonic
- 6. Wire Diameter: steady secure, quickly connected, easily disassemble
- 7. High Brightness 120 degree beam angle, flicker free, UGR<19, 0-10V / DALI dimming Function, CE RoHs, 5 years warranty

4. Feature:

- 1.80%~90% energy saving than incandescent lamp,
- 2. Anti-shock, anti-moisture.
- 3. Advanced constant current driver.
- 4. No flickering, No RF interference, No UV radiation,
- 5. Body termerature less than 53 °C,
- 6. Easy installation, maintenance free.
- 7. Professional thermal management.
- 8. Great heat dissipation due to unique structural design.

5. Applications:

- 1. Store, plaza, supermarket, mall, warehouse lighting.
- 2. School, office, meeting room, hospital, residential lighting.
- 3. Restaurant, hotel bedroom, dining room, bar, hall, lobby lighting.
- 4. Show room, counter, display window, museum lighting, etc.

5. Assurance:

- 1. 100% product quality protection
- 2. 100% on-time shipment protection
- 3. 100% payment protection for your covered amount

6. Shipping method:

- 1. By Express: DHL, TNT, UPS, Fedex, EMS, a fast and safe way for shipping, normally 3-5 working days for delivery
- 2. By Air: In some area, the shipping cost by air is more favorable than by Express; 5-7 days for delivery;

3. By Sea: the most economic shipping method, but cost longer shipping time; large quantity, heavy and not urgent goods can choose this way.

for more products please visit us on solarpanelstreetlight.com



